

1. Identification

Product identifier BernzOmatic AL-3 Aluminum Brazing Rod

Other means of identification

SDS number WC044

Recommended use Brazing rod.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Worthington Cylinder Corporation

Address 200 Old Wilson Bridge Road

Columbus, OH 43085

United States

Email: cylinders@worthingtonindustries.com

Telephone Number: 866-928-2657

CHEMTREC - 24 HOURS:

Within US and Canada 800-424-9300

Outside US and Canada +1 703-741-5970 (collect calls accepted)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement None.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash thoroughly after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Zinc	7440-66-6	93
Aluminum	7429-90-5	3.75-4.2
Copper	7440-50-8	2.2-2.85

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.
Skin contact	Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. If skin rash or an allergic skin reaction develops, get medical attention.
Eye contact	Rinse immediately with plenty of water for at least 15 minutes. Remove any contact lenses. Get medical attention if irritation develops or persists.
Ingestion	Immediately rinse mouth and drink a cupful of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Dust and fumes may irritate eyes, skin and upper respiratory tract. Contact with molten material may cause thermal burns.
Indication of immediate medical attention and special treatment needed	Treat symptomatically. Exposure may aggravate pre-existing respiratory disorders. Symptoms may be delayed.
General information	Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder. Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Do not use water or halogenated extinguishing media.
Specific hazards arising from the chemical	Fire or high temperatures create: Metal oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do it without risk.
General fire hazards	Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear protective clothing as described in Section 8 of this SDS. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Local authorities should be advised if significant spillages cannot be contained. For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. Recover and recycle, if practical. Keep out of water supplies and sewers.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water. If release occurs in the U.S. and is reportable under CERCLA Section 103, notify the National Response Center at (800)424-8802 (USA) or (202)426-2675 (USA).

7. Handling and storage

Precautions for safe handling	Wear appropriate personal protective equipment (See Section 8). Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with skin and eyes. Do not get this material on clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to the environment. Any surface that comes in contact with molten metal must be preheated or specially coated and rust free. Inadvertent contaminants to product such as moisture, ice, snow, grease, or oil can cause an explosion when charged to a molten metal bath or metal furnace (preheating metal will remove moisture from product).
Conditions for safe storage, including any incompatibilities	Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed container away from incompatible materials. Keep out of reach of children. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m ³ 15 mg/m ³	Respirable dust. Total dust.
Copper (CAS 7440-50-8)	PEL	1 mg/m ³ 0.1 mg/m ³	Dust and mist. Fume.

ACGIH

Components	Type	Value	Form
Copper (CAS 7440-50-8)	TWA	1 mg/m ³ 0.2 mg/m ³	Dust and mist. Fume.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m ³ 5 mg/m ³ 10 mg/m ³	Welding fume or pyrophoric powder. Respirable. Total
Copper (CAS 7440-50-8)	TWA	1 mg/m ³	Dust and mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

No exposure standards allocated.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Keep melting/soldering temperatures as low as possible to minimize the generation of fume. Shower, hand and eye washing facilities near the workplace are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Wear a face shield when working with molten material.

Skin protection

Hand protection

Wear protective gloves (i.e. latex, nitrile, neoprene).

Other

Chemical resistant clothing is recommended.

Respiratory protection

Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the OEL. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Heat resistant/insulated gloves and clothing are recommended when working with molten material.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Solid.

Form

Solid.

Color

Silver. Bluish-white.

Odor

Odorless.

Odor threshold

Not available.

pH

Not applicable.

Melting point/freezing point

Not available.

Initial boiling point and boiling range	2400 °F (1315.56 °C)
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	Non flammable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	6.7
Solubility(ies)	
Solubility (water)	Not soluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials. Avoid molten metal contact with water.
Incompatible materials	Strong acids. Strong alkalis.
Hazardous decomposition products	Toxic metal oxides are emitted when heated above the melting point.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the mucous membranes and respiratory tract. Lung damage and possible pulmonary edema can result from dust exposure. Inhalation of fumes may cause a flu-like illness called metal fume fever.
Skin contact	Dust may irritate skin. Contact with molten material may cause thermal burns.
Eye contact	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye.
Ingestion	Ingestion of dusts generated during working operations may cause nausea and vomiting. Copper poisoning can result in hemolytic anemia and kidney, liver and spleen damage.

Symptoms related to the physical, chemical and toxicological characteristics	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye, mucous membranes and respiratory tract. Contact with molten material may cause thermal burns.
---	--

Information on toxicological effects

Acute toxicity High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of metal fume fever. When heated, the vapors/fumes given off may cause respiratory tract irritation. Acute overexposure to Copper dust/fume can cause irritation of the eyes, nose, throat, and skin and under severe fume overexposure can cause metal fume fever with flu-like symptoms such as sweet metal taste, dry throat, coughing, fever and chills, tight chest, dyspnea, headache, blurred vision, back pain, nausea, vomiting, fatigue. Symptoms usually disappear within 24 hours. Copper may cause skin and hair discoloration. Inhalation of copper dusts may change the gums and mucous lining of the mouth which is generally attributable to localized tissue effect rather than general toxicity.

Components	Species	Test Results
Aluminum (CAS 7429-90-5)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 0.888 mg/l, 4 hours
Zinc (CAS 7440-66-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 5410 mg/m3
Skin corrosion/irritation	Dust may irritate skin.	
Serious eye damage/eye irritation	Elevated temperatures or mechanical action may form dust and fumes which may be irritating to the eye.	
Respiratory or skin sensitization		
Respiratory sensitization	No sensitizing effects known.	
Skin sensitization	No sensitizing effects known.	
Germ cell mutagenicity	No data available.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
	Not listed.	
Reproductive toxicity	No data available.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not relevant, due to the form of the product.	
Further information	No other specific acute or chronic health impact noted.	

12. Ecological information

Ecotoxicity Alloys in massive forms present a limited hazard for the environment. The product contains a substance which is very toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Components	Species	Test Results
Zinc (CAS 7440-66-6)		
Aquatic		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	0.24 mg/l, 96 hours
Persistence and degradability	The product is not biodegradable.	
Bioaccumulative potential	No data available.	
Mobility in soil	Alloys in massive forms are not mobile in the environment.	
Other adverse effects	None expected.	

13. Disposal considerations

Disposal instructions Dispose in accordance with all applicable regulations.
Local disposal regulations Dispose of in accordance with local regulations.
Hazardous waste code Waste codes should be assigned by the user based on the application for which the product was used.

Waste from residues / unused products Dispose of in accordance with local regulations. Scrapped material should be sent for refining to recover precious metal content. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations Under some use conditions, this material may be considered to be hazardous in accordance with OSHA 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8) LISTED
Zinc (CAS 7440-66-6) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Zinc	7440-66-6	93
Aluminum	7429-90-5	3.75-4.2
Copper	7440-50-8	2.2-2.85

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Aluminum (CAS 7429-90-5)
Copper (CAS 7440-50-8)
Zinc (CAS 7440-66-6)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Zinc (CAS 7440-66-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Zinc (CAS 7440-66-6)

US. Rhode Island RTK

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Zinc (CAS 7440-66-6)

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	30-June-2015
Revision date	-
Version #	01
Further information	HMIS® is a registered trade and service mark of the NPCA.
HMIS® ratings	Health: 1 Flammability: 0 Physical hazard: 0

NFPA ratings



References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

All information in this Material Safety Data Sheet is believed to be accurate and reliable. However, no guarantee or warranty of any kind is made with regard to the accuracy of information or the suitability of the recommendations contained herein. It is the user's responsibility to assess the safety and toxicity of this product under their own conditions of use and to comply with all applicable laws and regulations.